



MODEL: AIR0500

Standard Chiller Specifications

| | |
|----------------------------|--------------------|
| Model Number | AIR0500 |
| Capacity | 6,000 BTU's/hr |
| Inlet/Outlet Piping | 1/2" NPT |
| Pump Specs | 4 GPM at 50 PSI |
| Voltage | 110V or 230/1 |
| Rated Load Amps | 14.7A@110V |
| Dimensions | 21"L x 15"W x 28"H |
| Weight | 150 lbs (approx.) |

Standard Chiller Features

- Rated at ambient temperatures from 35° F to 100° F
- Hermetically sealed compressor
- Continuous duty, non-ferrous pump, 4 GPM at 50 PSI (other pumps available)
- Non-ferrous piping system
- Submersed copper coil evaporator
- Stainless steel tank with fully welded stainless steel couplers (3.5 gallon capacity)
- Environmentally acceptable R134a refrigerant
- Powder-coated steel cabinet (stainless steel is also available)
- Available voltages: 110v or 230/1
- Standard 110V cord and plug for electrical connections (or as 230/1 twist plug)
- Mounted on casters (feet option available)

1-800-CHILLER

www.fluidchillers.com | 1-517-484-9190 | 2730 Alpha Access Drive | Lansing, MI 48910



MODEL AIR0500 SPECIFICATION SHEET

Chiller:

Air cooled stand alone chiller designed for indoor operation. Capacity is 6,000 BTU's/hr at rated conditions. Set up for ambient temperatures 35° F to 100° F (for higher or lower ambient conditions please consult factory).

Compressor/Condensing Unit: *Copeland Condensing Unit*

Fluid Chillers has determined this to be the most energy efficient and reliable in this size.

Pump:

This chiller is equipped with a continuous duty, non-ferrous pump. Set up to deliver 4GPM at 50 PSI. The fluid types are to be water or water/glycol (for other fluids consult factory). Output pressure gauge is standard.

Evaporator:

Submersed copper coil continuously formed. This has proven itself to be the most reliable design in the industry. It is less susceptible to freezing and fluid contaminations.

Reservoir:

Stainless steel tank with fully welded stainless steel couplers; it will include: drain, sight glass, and manual fill tube. The sight glass is easily visible from the exterior of the chiller.

Electrical:

- Available as 115v/1/50-60Hz or 230/1/50-60Hz
- On/Off
- RLA= 15 AMPS@ 110V, 8 AMPS@ 230/1

Refrigeration:

- This series of chillers is totally self-contained and requires only a power connection
- High side filter drier
- Thermostatic expansion valve
- Liquid line sight glass
- High and low side pressure switches
- Full refrigerant charge
- Environmentally friendly R-134A

Included Features:

- Unit comes on 4 casters for easy mobility
- Comes standard with a Carel microprocessor temperature controller with LED display
- Dimensions and Footprint:
 - 21"L x 15"W x 28"H
 - Dry weight = 150 lbs (approx)
 - ½" NPT, stainless steel inlet/outlet connections

1-800-CHILLER

www.fluidchillers.com | 1-517-484-9190 | 2730 Alpha Access Drive | Lansing, MI 48910