

MODEL: AIR30,000



Standard Chiller Specifications

Model Number	AIR30,000
Capacity	370,000 BTU's/hr
Inlet/Outlet Piping	2" NPT
Pump Specs	70 GPM at 45 PSI
Voltage/Phase	460/3 (All Voltages Available)
Rated Load Amps	57A @460/3
Dimensions	86"L x 50"W x 90"H
Weight	1990 lbs (approx.)

Standard Chiller Features

- These units can be made for indoor or outdoor installation
- Rated at ambient temperatures from 15° F to 100° F (for higher or lower ambient please consult factory)
- Hermetically sealed scroll compressor (other options available)
- Continuous duty, horizontal TEFC, 70 GPM at 45 PSI (other pumps available)
- Non-ferrous and ferrous piping available
- Stainless steel evaporator (other evaporator options available)
- Stainless steel tank w/ fully welded stainless steel couplers (120g tank option)
- Galvanized steel cabinet (powdered coated and stainless steel available)
- Available voltages:230/3, 460/3 (all voltages available upon request)
- Single point electrical connection into disconnect
- NEMA 12/4 electrical enclosure, fully gasketed with lockable disconnect
- Mounting base standard

1-800-CHILLER



MODEL AIR30,000 SPECIFICATION SHEET

Chiller: *(Vertical Air Discharge)*

Air cooled stand alone chiller designed for indoor operation. Capacity is 301,000 BTU's/hr at rated conditions. Set up for ambient temperatures 35° F to 100° F (for higher or lower ambient conditions please consult factory). Outdoor units have lower ambient rating.

Compressor: *(High Efficient Scroll Compressor)*

Fluid Chillers has determined this to be the most energy efficient and reliable in this size.

Pump: *(70 GPM@ 45 PSI to Process) (Other Pump Options Available)*

This chiller is equipped with a high efficient, pump and TEFC motor. The fluid types are to be water or water/glycol (for other fluids consult factory). Output pressure gauge is standard. Manual bypass to allow customer to adjust output pressure and flow is standard.

Reservoir: *(120 Gallon Standard)*

Stainless steel tank with fully welded stainless steel couplers; it will include: drain, sight glass, and manual fill tube. The sight glass is easily visible from the exterior of the chiller.

Electrical:

- Available as 230/1/50-60Hz, 230/3/50-60Hz, 460/3/50-60Hz (all voltages available)
- Remote Start/Stop
- RLA= 57 Amps@ 460/3
- FLA= 80 Amps@ 460/3
- NEMA 12/4, electrical enclosure, fully gasketed with lockable disconnect
- Built to standard industrial practices utilizing IEC components

Refrigeration:

- This series of chillers is totally self-contained and requires only a power connection
- High side filter drier
- Thermostatic expansion valve
- Liquid line sight glass
- High and low side pressure switches
- Full refrigerant charge
- Environmentally friendly refrigerant
- Multiple Schrader access points
- Vibration isolators
- Stainless steel evaporator
- High and low side pressure gauges

Included Features:

- Protection screen on air inlet
- Comes standard with a microprocessor temperature controller with LCD display
- Dimensions and Footprint:
 - 86"L x 50"W x 90"H
 - Dry weight = 1990 lbs (approx)
 - 2" NPT, stainless steel inlet/outlet connections

1-800-CHILLER

www.fluidchillers.com | 1-517-484-9190 | 2730 Alpha Access Drive | Lansing, MI 48910